

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** OVEN CLEANER RTU**Product code:** 7574/02**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet**

Company name: Greyland Ltd
Unit 9
Fifth Avenue
Tameside Park Industrial Estate
Dukinfield
Cheshire
SK16 4PP

Tel: +44 (0) 161 343 3830**Fax:** +44 (0) 161 343 0608**Email:** sales@greyland.co.uk**1.4. Emergency telephone number****Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** Skin Corr. 1A: H314**Most important adverse effects:** Causes severe skin burns and eye damage.**2.2. Label elements****Label elements:****Hazard statements:** H314: Causes severe skin burns and eye damage.**Signal words:** Danger**Hazard pictograms:** GHS05: Corrosion**Precautionary statements:** P280: Wear protective gloves.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405: Store locked up.

SAFETY DATA SHEET

OVEN CLEANER RTU

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DISODIUM METASILICATE

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|-----------|-----------|--------------------------------------|---------|
| 229-912-9 | 6834-92-0 | - | Skin Corr. 1B: H314; STOT SE 3: H335 | 1-10% |

2-(2-BUTOXYETHOXY)ETHANOL

| | | | | |
|-----------|----------|---|--------------------|-------|
| 203-961-6 | 112-34-5 | - | Eye Irrit. 2: H319 | 1-10% |
|-----------|----------|---|--------------------|-------|

2-BUTOXYETHANOL

| | | | | |
|-----------|----------|---|---|-------|
| 203-905-0 | 111-76-2 | - | Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 | 1-10% |
|-----------|----------|---|---|-------|

SODIUM XYLENE SULPHONATE

| | | | | |
|---|-----------|---|---|-------|
| - | 1300-72-7 | - | - | 1-10% |
|---|-----------|---|---|-------|

PRIMARY ALCOHOL ETHOXYLATE

| | | | | |
|---|---|---|--------------------------------------|-------|
| - | - | - | Eye Dam. 1: H318; Acute Tox. 4: H302 | 1-10% |
|---|---|---|--------------------------------------|-------|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

[cont...]

SAFETY DATA SHEET

OVEN CLEANER RTU

Page: 3

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET

OVEN CLEANER RTU

Page: 4

8.1. Control parameters

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------------------|-------------------------|------------|--------------|
| UK | 67.5 mg/m ³ | 101.2 mg/m ³ | - | - |

2-BUTOXYETHANOL

| | | | | |
|----|--------|--------|---|---|
| UK | 25 ppm | 50 ppm | - | - |
|----|--------|--------|---|---|

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-green

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Flash point°C: >70

pH: 12.0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET

OVEN CLEANER RTU

Page: 5

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DISODIUM METASILICATE

| | | | | |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 770 | mg/kg |
| ORL | RAT | LD50 | 1153 | mg/kg |

2-(2-BUTOXYETHOXY)ETHANOL

| | | | | |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 6050 | mg/kg |
| ORL | RAT | LD50 | 4500 | mg/kg |

2-BUTOXYETHANOL

| | | | | |
|-----|-----|------|------|-------|
| IVN | RAT | LD50 | 307 | mg/kg |
| ORL | MUS | LD50 | 1230 | mg/kg |
| ORL | RAT | LD50 | 470 | mg/kg |

SODIUM XYLENE SULPHONATE

| | | | | |
|-----|-----|------|-------|-------|
| ORL | RAT | LD50 | >7000 | mg/kg |
|-----|-----|------|-------|-------|

PRIMARY ALCOHOL ETHOXYLATE

| | | | | |
|-----|-----|------|-----------|-------|
| ORL | RAT | LD50 | >200<2000 | mg/kg |
|-----|-----|------|-----------|-------|

Relevant hazards for substance:

| Hazard | Route | Basis |
|---------------------------|-------|-----------------------|
| Skin corrosion/irritation | DRM | Hazardous: calculated |

[cont...]

SAFETY DATA SHEET

OVEN CLEANER RTU

Page: 6

| | | |
|-------------------------------|-----|-----------------------|
| Serious eye damage/irritation | OPT | Hazardous: calculated |
|-------------------------------|-----|-----------------------|

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

PRIMARY ALCOHOL ETHOXYLATE

| | | | |
|------|----------|------|------|
| FISH | 96H LC50 | 1-10 | mg/l |
|------|----------|------|------|

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

[cont...]

SAFETY DATA SHEET

OVEN CLEANER RTU

Page: 7

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.
(DISODIUM METASILICATE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.